



***Thermotec Closed Cell  
Backing Rod***



Thermotec Closed Cell Backing Rod is manufactured from closed cell low density polyethylene foam. The product is manufactured in a range of sizes and has excellent compression and recovery properties

Material:	Low density polyethylene closed cell foam
Density:	40-50kg/m <sup>3</sup> nominal
Service Temperature:	-40C to +90C
Water Absorption:	<2% by volume after 28 days submersion
Compression Recovery:	Excellent – 95%
Compression Deflection:	Excellent - >20.5KPa
Compression Resistance:	Excellent - <335kPa
Flexibility:	Excellent

- Compatible with all leading Sealants
- Available in full range of diameters – 6mm to 50mm (60mm & 70mm available on request)
- Excellent rebound recovery
- Round profile enables sealant to form correct profile for optimum movement
- Minimises the amount of sealant required
- Suitable for horizontal and vertical joints, internal walls, and glass applications
- Low moisture absorption
- Does not discolour or stain
- Non-adhering to sealants
- Made in Australia

	STOCK CODE	Diameter (mm)	No. of coils per carton	Coil/Length (metre)	Metres per carton
<b>Backing Rod</b>					
	<a href="#">424970006135</a>	6	6	250	1500
	<a href="#">424970011135</a>	10	5	200	1000
	<a href="#">424970013135</a>	13	5	100	500
	<a href="#">424970015135</a>	15	4	100	400
	<a href="#">424970020135</a>	20	3	60	180
	<a href="#">424970025135</a>	25	3	50	150
	<a href="#">424970030135</a>	30	2	50	100
	<a href="#">424970040135</a>	40	80	2	160
	<a href="#">424970050135</a>	50	50	2	100