


Thermotec Closed Cell
Backing Rod



Thermotec Closed Cell Backing Rod is manufactured from closed cell low density polyethylene foam. The product is manufactured in a range of sizes and has excellent compression and recovery properties

Material:	Low density polyethylene closed cell foam
Density:	40-50kg/m ³ nominal
Service Temperature:	-40C to +90C
Water Absorption:	<2% by volume after 28 days submersion
Compression Recovery:	Excellent – 95%
Compression Deflection:	Excellent - >20.5KPa
Compression Resistance:	Excellent - <335kPa
Flexibility:	Excellent

- Compatible with all leading Sealants
- Available in full range of diameters – 6mm to 50mm (60mm & 70mm available on request)
- Excellent rebound recovery
- Round profile enables sealant to form correct profile for optimum movement
- Minimises the amount of sealant required
- Suitable for horizontal and vertical joints, internal walls, and glass applications
- Low moisture absorption
- Does not discolour or stain
- Non-adhering to sealants
- Made in Australia

	STOCK CODE	Diameter (mm)	No. of coils per carton	Coil/Length (metre)	Metres per carton
Backing Rod					
	424970006135	6	6	250	1500
	424970011135	10	5	200	1000
	424970013135	13	5	100	500
	424970015135	15	4	100	400
	424970020135	20	3	60	180
	424970025135	25	3	50	150
	424970030135	30	2	50	100
	424970040135	40	80	2	160
	424970050135	50	50	2	100