


Thermotec Closed Cell
Black Backing Rod



Thermotec Closed Cell Black Backing Rod is manufactured from closed cell low density polyethylene foam. The product is manufactured in a range of sizes and has excellent compression and recovery properties with low visibility making it ideal for the glazing & facades industries

Material:	Low density polyethylene closed cell foam
Density:	40-50kg/m ³ nominal
Service Temperature:	-40C to +90C
Water Absorption:	<2% by volume after 28 days submersion
Compression Recovery:	Excellent – 95%
Compression Deflection:	Excellent - >20.5KPa
Compression Resistance:	Excellent - <335kPa
Flexibility:	Excellent

- Compatible with all leading Sealants
- Available in selected diameters – 6mm, 10mm & 15mm
- Excellent rebound recovery
- Round profile enables sealant to form correct profile for optimum movement
- Minimises the amount of sealant required
- Suitable for horizontal and vertical joints, internal walls, and glass applications
- Low moisture absorption
- Black for low visibility
- Non-adhering to sealants
- Made in Australia

	STOCK CODE	Diameter (mm)	No. of coils per carton	Coil/Length (metre)	Metres per carton
Black Backing Rod					
	424970006125	6	6	250	1500
	424970010125	10	4	250	1000
	424970015125	15	4	100	400

